



公差等级/General	tolerance/(mm)	0	>3	>6	>10	>18	>30	>50	>80	>120	>180	>250	>315	>400	>500	0.1/1/10
~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	~	±Z
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±Z	±Z	±Z

4	Pin Header	Copper Alloy	Sn Plated
3	Screw	Steel	M3/Zn Plated
2	Cage	Copper Alloy	M3/Ni Plated
1	Housing	PA66	UL94V-0
ITEM	NAME OF PART	MATERIAL	NOTES
UL 标准/UL Standard:	B	C	D
额定电压/电源/Rated Voltage(V)/Current(A)	300/12	/	/
IEC 标准/IEC Standard:	/	/	/
过压类别/Overvoltage Category/污染等级	/	III/2	/
额定电压/电源/Rated Voltage(V)/Current(A)	/	250/15	/
工频耐压/Withstanding Voltage(kV/min)	/	AC2000	/
螺丝扭矩/Torque Tightening(N·m/Lb·in)	M3	0.2P 0.34/3.04	≥0.3P 0.5/4.43
线径范围(裸线铜线)/Wire Range(rigid and flexible)(mm² /AWG)	0.2~1.5/26~14		
间距/Pitch(mm)/线径范围/oles	5.08/N=02~24P		
剥线长度/Stripping length(mm)	6~7		
使用温度范围/Operating Temperature(°C)	-40~+105		
符合RoHS要求/Conform to RoHS	Yes		
标准颜色编号/Standard color number.	/		
PANTONE / RAL	/		

MATERIAL: / SURFACE: /

MAT NO.: /

STATUS: /

APPD: LiGL 2020.06.23 NAME: **DEGSON® NINGBO DEGSON ELECTRICAL CO., LTD**

CHKD: Mek 2020.06.23 **DG127H-5.08-XXP-1Y-00A(H)**

DRAFT: Joy.z 2017.07.12 DRAWING NO.: DG127H-5.08-C01

TYPE: CUSTOMER DRAWING SCALE: 2.5:1 SHEET 1/1

REV ECN DESCRIPTION

DRAFT DATE

SIZE: A4

SCALE: 2.5:1 SHEET 1/1

D

C

B

A

D

C

B

A